

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPOTLIGHT

Supplier's address: Dimitris Papadopoulos, Rodopoleos 30, 16777 Athens Elliniko, EL

Model identifier: 5406

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	Other electric interface		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	6	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	480 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P_{on}), expressed in W	6,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control	Height	15	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	70	
	Depth	70	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,381 0,380
Parameters for LED and OLED light sources:			
R9 colour rendering index value	6	Survival factor	0,85
the lumen maintenance factor	0,85		

(a) : not applicable;


(b) : not applicable;

LED Test Report

Product Mark

Product Type :RR-24W-4000K
 Temperature : 'C
 Operator :
 Remark:

Manufacturer :
 Humidity : 65%
 Test Date :2021-10-16 13:32:09



Chroma Parameters

Chro.Coor.:x=0.3813 y=0.3733 u=0.2271 v=0.3335 duv=-0.0019
 CCT: 3949K Dominant Wave.:580.3nm Purity:26.5%
 Flux RGB Ratio:R=18.4%,G=79.4%,B=2.2% Peak Wave:449.5nm Half Width:21.3nm

Rendering Index:Ra= 81.5

R1 =80	R2 =87	R3 =92	R4 =82	R5 =81	R6 =83	R7 =84	R8 =63
R9 =6	R10=69	R11=81	R12=61	R13=81	R14=96	R15=74	

Photo Parameters

Flux:1683.51lm Effi.:84.6lm/W Radiant:5809.1mW Iv:0.0mcd
 Efficiency:0.161 Effi Level:A+ (EU 874-2012)

Ele. Parameters

Voltage:U=220.000V Current:I=0.1720A
 Power:P=19.89W Power Factor:PF=0.523

Instrument state

Instrument:HP8000S Integral Time: 413.347ms VPeak: 13463
 VDark: 1193 Scan Range: 380-780nm Product ID: 9154