

Supplier	TOSHIBA
----------	---------

Indoor unit	RAS-24E2KVG-E
-------------	---------------

Outdoor unit	RAS-24E2AVG-E
--------------	---------------

## Sound power level

indoor unit (cooling)	dB	61
-----------------------	----	----

outdoor unit (cooling)	dB	67
------------------------	----	----

indoor unit (heating)	dB	61
-----------------------	----	----

outdoor unit (heating)	dB	67
------------------------	----	----

## Refrigerant

Type		R32
------	--	-----

Global Warming Potential	kgCO <sub>2</sub> eq	675
--------------------------	----------------------	-----

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO<sub>2</sub>, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

## Cooling

Energy efficiency class		A++
-------------------------	--	-----

Design load (P <sub>designc</sub> )	kW	6.5
-------------------------------------	----	-----

Seasonal efficiency (SEER)		6.90
----------------------------	--	------

Seasonal electricity consumption (Q <sub>CE</sub> ) (*)	kWh/annum	330
---	-----------	-----

(\*) Based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located

## Heating

		Heating/Average	Heating/Warmer	Heating/Colder
Energy efficiency class		A+	A+++	x
Design load (Pdesignh)	kW	5.4	2.9	x,x
Seasonal efficiency (SCOP)		4.30	5.30	x,xx
Seasonal electricity consumption (Q <sub>HE</sub> ) (*)	kWh/annum	1757	759	x
Back up heating capacity	kW	0.96		
<b>Declared capacity for heating, at indoor temperature 20°C and outdoor temperature Tj.</b>				
Tj= -7°C (Pdh)	kW	4.78	-	x,xx
Tj= 2°C (Pdh)	kW	2.91	2.90	x,xx
Tj= 7°C (Pdh)	kW	1.87	1.86	x,xx
Tj= 12°C (Pdh)	kW	1.00	1.00	x,xx
Tj=bivalent temperature (Pdh)	kW	4.78	2.90	x,xx
Tj=operation limit (Pdh)	kW	3.88	3.88	x,xx
Tj= -15°C (Pdh)	kW	-	-	x,xx

(\*) Based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located