
Printing date 05.11.2019

Version: 1

Revision: 04.11.2019

(Contd. on page 2)

GB



· Classification according to Regulation (EC) No 1272/2008

STOT SE 3 H336

Asp. Tox. 1 H304

· 2.2 Label elements

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

May be fatal if swallowed and enters airways.

• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

May cause drowsiness or dizziness.

Version: 1

Printing date 05.11.2019

Trade name: WOOD DOCTOR UV

Revision: 04.11.2019

(Contd. of page 1)

· Hazard	pictograms	



· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, terpene processing by-products

# · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness. • Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

*P501* Dispose of contents/container in accordance with local/regional/national/international regulations.

#### • Additional information:

Contains Hydrocarbons, terpene processing by-products. May produce an allergic reaction.

- 2.3 Other hazards The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.
- · Results of PBT and vPvB assessment

· PBT: Not applicable.

• **vPvB:** Not applicable.

#### CECTION 1

## **SECTION 3: Composition/information on ingredients**

- 3.2 Chemical characterisation: Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-48-9 EC number: 919-857-5 Reg.nr.: 01-2119463258-33-XXXX	Hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	25-50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 012119486944-21-xxxx	propane Flam. Gas 1, H220 Press. Gas C, H280	10-25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane (< 0.1% butadine) Flam. Gas 1, H220 Press. Gas C, H280	10-25%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane (<0.1% butadine) Flam. Gas 1, H220 Press. Gas C, H280	1-2.5%
CAS: 68956-56-9	Hydrocarbons, terpene processing by-products Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1, H317	0.1-1%

Ingredients according to Detergents Regulation 648/2004/EC For the wording of the listed hazard phrases refer to section 16.

# **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact: If skin irritation continues, consult a doctor.

· After swallowing: Seek immediate medical advice.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

<sup>•</sup> General information: Immediately remove any clothing soiled by the product.

Printing date 05.11.2019

Version: 1

Revision: 04.11.2019

#### Trade name: WOOD DOCTOR UV

(Contd. of page 2) • **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

**SECTION 5: Firefighting measures** 

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- Protective equipment: No special measures required.
- Additional information Cool endangered receptacles with water spray.

#### **SECTION 6:** Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

#### 6.4 Reference to other sections

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling Keep away from heat and direct sunlight.
- Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding  $50^{\circ}$ C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane (< 0.1% butadine) (10-25%)

WEL (Great Britain) Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.
- Respiratory protection:

*Filter AX Filter A*  Version: 1

Printing date 05.11.2019

Trade name: WOOD DOCTOR UV

• Protection of hands:

• *Material of gloves* The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can

not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Not suitable are gloves made of the following materials: Strong material gloves

## **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and c	hemical properties
General Information	
· Appearance:	
Form:	Aerosol
Colour:	Light yellow
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	:: 41 °C
· Flash point:	-19 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	240 °C
• Decomposition temperature:	Not determined.
• Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are
	possible.
• Explosion limits:	
Lower:	0.6 Vol %
Upper:	7 Vol %
· Vapour pressure at 20 °C:	2.5 hPa
· Density at 20 °C:	$0.77863 \text{ g/cm}^3$
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Insoluble.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	48.9 %
EU-VOC:	681.3 g/l
EU-VOC	87.50 %
Swiss VOC:	87.50 %
• 9.2 Other information	No further relevant information available.
	······································

## **SECTION 10: Stability and reactivity**

• 10.1 Reactivity No further relevant information available.

(Contd. on page 5) GB

(Contd. of page 3)

Revision: 04.11.2019

Printing date 05.11.2019

Version: 1

Revision: 04.11.2019

#### Trade name: WOOD DOCTOR UV

(Contd. of page 4)

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### **SECTION 11: Toxicological information**

• 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

## · LD/LC50 values relevant for classification:

64742-48-	64742-48-9 Hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Oral	LD50	>5,000 mg/kg (Rat)	
Dermal	LD50	>5,000 mg/kg (rab)	
Inhalative	LC50 / 4 h	>4,951 mg/l (Rat)	
Primary irritant effect:			
Skin corrosion/irritation Based on available data, the classification criteria are not met.			
· Serious eye damage/irritation Based on available data, the classification criteria are not met.			
n • /			

- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. The material is harmful to the environment.

- · 12.5 Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

- 13.1 Waste treatment methods
- · Recommendation Disposal must be made according to official regulations

#### · European waste catalogue

	8
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING
	NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 04	metallic packaging
20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND
	INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)

(Contd. on page 6)

Printing date 05.11.2019

Version: 1

Revision: 04.11.2019

(Contd. of page 5)

# Trade name: WOOD DOCTOR UV

## 20 01 13\* solvents

• Uncleaned packaging: • Recommendation: Disposal in accordance with administrative provisions

14.1 UN-Number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR	1950 AEROSOLS
IMDG	AEROSOLS (Hydrocarbons, terpene processing by-products),
	MARINE POLLUTANT
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
IMDG	
Class	2.1
Label	2.1
Class	2.1
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	Yes
Service and in a (ADD).	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	- E D S U
EMS Number: Stowage Code	F-D,S-U SW1 Protected from sources of heat.
Slowuge Coue	SW1 Protected from sources of neat. SW2 Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation Cour	Segregation as for class 9. Stow "separated from" class 1 excep
	for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Annex II of	f Marpol and

GB

Version: 1

Printing date 05.11.2019

Revision: 04.11.2019

#### Trade name: WOOD DOCTOR UV

	(Contd. of pa
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
·IMDG	
· Limited quantities (LQ)	1L
$\cdot$ Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

#### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Reg. (EC) n. 1272/2008 - CLP;
Reg. (EC) n. 1907/2006 - Reach;
Reg. (EC) n. 2015/830 annex II of REACH;
Reg. (EC) n. 648/04 (Detergents);
Reg. (EC) n. 528/12 (Biocides BPR);
Reg. (EC) n. 1223/2009 (Cosmetics);
Dir. 06/08 ADR - RID - IMDG - IATA;
Dir. 47/08 (Aerosols); Dir. 12/18 (Seveso III);
Dir. 2008/98/CE and Reg. (EC) n.1357/2014 (Waste management)

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

• Technical instructions (air):

Class	Share in %
NK	75-100

• Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

# • Department issuing SDS:

Customer Service NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

(Contd. on page 8)

Version: 1

Trade name: WOOD DOCTOR UV

(Contd. of page 7) · Contact: Customer Service NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011 Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds) VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols – Category I Press. Gas C: Gases under pressure – Compressed gas Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 \* Data compared to the previous version altered.

#### Revision: 04.11.2019

Printing date 05.11.2019