

# GREASE SPRAY

## HIGH-QUALITY MULTI-FUNCTIONAL WHITE GREASE BASED ON PTFE.



**Temperature resistance:** From -30°C to +125°C.

### TECHNICAL SPECIFICATIONS

**Chemical base:** Lithium and calcium grease with mineral oils and P.T.F.E.

**Viscosity:** Pasty

### STORAGE CONDITIONS

A minimum of 36 months. Close the container properly and store in a dry, cool and frost-free location.

### PRODUCT DESCRIPTION

High-quality multi-functional white grease based on PTFE.

### FIELD OF APPLICATION

For lubrication and protection of all types of sliding, ball and roller bearings, shafts, chains, gears, hinges and other rotating parts. Mechanically very stable at high pressure and high operating temperatures.

### PROPERTIES

- Resistant to high mechanical and thermal loads
- Rust and corrosion resistant
- Water resistant
- Water repellent
- Acid-free
- With extra precision spray hose

### PREPARATION

**Preliminary surface treatment:** Make sure that the surface is clean, dry, and free of grease.

### APPLICATION

#### Directions for use:

Shake well before use. Spray surface(s) evenly from a distance of approx. 10-20 cm.

**Stains/residue:** Remove stains with Bison Cleaner Spray or degreaser.

**Points of attention:** Use the additional spray hose integrated in the cap for optimum dosage.

### TECHNICAL PROPERTIES

Moisture resistance: Very good